

Immersion

DWH-MR


Dishwasher Applications

- 2" NPT Brass Screw Plug
- INCOLOY® Sheath Elements
- 52 - 56 W/In²
- 5 - 15 kW
- Integral Thermostat and Cutout
- 208, 240 and 480 Volt, Three Phase



SCREW PLUG

DWH-MR — Dimensions (Inches)



Applications

- Commercial Dishwashers
- Sterilizing Equipment
- Other Water Heating Applications

Features

- Integral SPST Thermostat (100 - 210°F) and Manual Reset Cutout
- Pilot Light
- On/Off Switch
- Moisture and Spray Resistant Hinged Terminal Enclosure
- Built-in Contactor (480V requires external 120V control circuit)
- Clamping Nut and Gasket supplied for mounting through tank wall up to 1/4" thick with a 2-7/8" diameter opening

Specifications and Ordering Information

kW	Volts	Phase	W/In ²	DIM B (In.)	Model	Stock	PCN	Wt. (Lbs.)
5	120	1	53	13-3/16	DWH-MR-5PS	NS	293000	11
5	208	1	53	13-3/16	DWH-MR-5PS	S	293085	11
5	240	1	53	13-3/16	DWH-MR-5PS	S	293106	11
7.5	208	1	52	18-7/8	DWH-MR-7.5PS	NS	293026	12
7.5	240	1	52	18-7/8	DWH-MR-7.5PS	NS	293034	12
10	208	1	53	24	DWH-MR-10PS	NS	293050	13
10	240	1	53	24	DWH-MR-10PS	NS	293069	13
5	208	3	53	13-3/16	DWH-MR-5PS	S	293093	11
5	240	3	53	13-3/16	DWH-MR-5PS	S	293114	11
5	480	3	53	13-3/16	DWH-MR-5PS	S	293018	11
7.5	208	3	52	18-7/8	DWH-MR-7.5PS	S	293122	12
7.5	240	3	52	18-7/8	DWH-MR-7.5PS	NS	293130	12
7.5	480	3	52	18-7/8	DWH-MR-7.5PS	S	293042	12
10	208	3	53	24	DWH-MR-10PS	NS	293149	13
10	240	3	53	24	DWH-MR-10PS	NS	293157	13
10	480	3	53	24	DWH-MR-10PS	S	293165	13
15	208	3	56	32-5/8	DWH-MR-15PS	NS	293077	17
15	240	3	56	32-5/8	DWH-MR-15PS	S	293173	17
15	480	3	56	32-5/8	DWH-MR-15PS	S	293181	17

Stock Status: S = stock AS = assembly stock NS = non-stock
To Order—Specify model, volts, phase, kW, PCN and quantity.